

HANDHELD	MOBILE		SHORT THROW			VALUE				MAINSTREAM		PERFORMANCE
DELL™ M109S On-The-Go	DELL™ M210X	DELL™ M410HD	DELL™ S300	DELL™ S300w	DELL™ S300wi	DELL™ 1210S	DELL™ 1410X	DELL™ 1510X	DELL™ 1610HD	DELL™ 4210X	DELL™ 4610X Wireless PLUS	DELL™ 7609WU
												
SVGA (858 x 600)	XGA (1024 x 768)	WXGA (1280 x 800)	WXGA (1280 x 800)	WXGA (1280 x 800)	WXGA (1280 x 800)	SVGA (800 x 600)	XGA (1024 x 768)	XGA (1024 x 768)	WXGA (1280 x 800)	XGA (1024 x 768)	XGA (1024 x 768)	WUXGA (1920 x 1200)
4:3	4:3	16:10	16:10	16:10	16:10	4:3	4:3	4:3	16:10	4:3	4:3	16:10
50	2000	2000	2200	2200	2200	2500	2700	3500	3500	3500	3500	3850
800:1	2100:1	2100:1	2400:1	2400:1	2400:1	2200:1	2200:1	2100:1	2100:1	2000:1	2000:1	2700:1
0.80 lbs (360g)	2.6 lbs (1.18kg)	2.6 lbs (1.18kg)	6.7 lbs (3.04kg)	6.8 lbs (3.08kg)	6.9 lbs (3.13kg)	5.3 lbs (2.4kg)	5.3 lbs (2.4kg)	5.2 lbs (2.36kg)	5.2 lbs (2.36kg)	6.35 lbs (2.88kg)	6.55 ± 0.05lbs (2.97 ± 0.02kg)	13.4 lbs (6.08kg)
16.7M	1.07B	1.07B	1.07B	1.07B	1.07B	1.07B	1.07B	1.07B	1.07B	16.7M	16.7M	Up to 1.07B (with Dithering)
R/G/B LED module	OSRAM 165W user-replaceable	OSRAM 165W user-replaceable	OSRAM E20.8 190W user-replaceable	OSRAM E20.8 190W user-replaceable	OSRAM E20.8 190W user-replaceable	Philips 185W user-replaceable	Osram 200W user-replaceable	Philips 225W user-replaceable	Philips 225W user-replaceable	Philips 280W user-replaceable	Philips 280W user-replaceable	300W user-replaceable
Up to 10000 (Typical)	Up to 3000 Typical / Up to 5000 Eco-Mode	Up to 3000 Typical / Up to 5000 Eco-Mode	Up to 5000 (Typical)	Up to 5000 (Typical)	Up to 5000 (Typical)	Up to 3000 Typical / Up to 4000 Eco-Mode	Up to 3000 Typical / Up to 4000 Eco-Mode	Up to 3000 Typical / Up to 4000 Eco-Mode	Up to 3000 Typical / Up to 4000 Eco-Mode	Up to 2000 Typical / Up to 2500 Eco-Mode	Up to 2000 Typical / Up to 2500 Eco-Mode	Up to 2000 Typical / Up to 2500 Eco-Mode
1.97	1.95 (wide) - 2.15 (tele)	1.55 (wide) - 1.7 (tele)	0.521 (wide and tele)	0.521 (wide and tele)	0.521 (wide and tele)	1.95 (wide) - 2.15 (tele)	1.95 (wide) - 2.15 (tele)	1.6 (wide) - 1.92 (tele)	1.28 (wide) - 1.536 (tele)	1.6 (wide) -1.92 (tele)	1.6 (wide) -1.92 (tele)	1.85 (wide) - 2.22 (tele)
15" - 60" (0.38m ~ 1.52m)	22.89" - 302.8" (0.58m ~ 7.69m)	27.2" - 361" (0.69m ~ 9.16m)	44.6" ~ 294" (1.13m ~ 7.46m)	44.6" ~ 294" (1.13m ~ 7.46m)	44.6" ~ 294" (1.13m ~ 7.46m)	22.9" - 303" (0.58m ~ 7.69m)	22.9" - 303" (0.58m ~ 7.69m)	30.8" - 307" (0.78m ~ 7.79m)	36.3" ~ 362" (0.92m ~ 9.19m)	30" - 307" (0.76m ~ 7.79m)	30" - 307" (0.76m ~ 7.79m)	20.9" - 301" (0.53m ~ 7.64m)
1.97 ft - 7.87 ft (0.6m - 2.4m)	3.3 ft - 39.4 ft (1.0m - 12.0m)	3.3 ft - 39.4 ft (1.0m - 12m)	1.64 ft ~ 10.83 ft (0.5 ~ 3.3 m)	1.64 ft ~ 10.83 ft (0.5 ~ 3.3 m)	1.64 ft ~ 10.83 ft (0.5 ~ 3.3 m)	3.28 ft ~ 39.37 ft (1m ~ 12m)	3.28 ft ~ 39.37 ft (1m ~ 12m)	3.94 ft - 32.81 ft (1.2m - 10m)	3.94 ft - 32.81 ft (1.2m - 10m)	3.9 ft - 32.8 ft (1.2m - 10m)	3.94 ft - 32.81 ft (1.2m - 10m)	3.28 ft - 39.37 ft (1.0m - 12m)
no	1W	1W	8W	8W	8W	2W	2W	8W	8W	2 x 5W	2 x 5W	2 x 5W
1x Multi-Input Cable for VGA input (analog/RGB/component, HDTV input signals)	1x AC power 1x D-Sub VGA-In 1x Composite Video RCA 1x S-Video 1x USB slave 1x Audio in 1x Audio out 1x HDMI	1x AC power 1x D-Sub VGA-In 1x Composite Video RCA 1x S-Video 1x USB slave 1x Audio in 1x Audio out 1x HDMI	1x AC power 2x D-Sub VGA-In 1x D-Sub VGA-Out 1x Composite Video RCA 1x S-Video 1x Mini USB slave 3x Audio in 1x Audio out 1x RJ45 1x HDMI 1x RS232 1x Microphone 1x 12V DC Relay output	1x AC power 2x D-Sub VGA-In 1x D-Sub VGA-Out 1x Composite Video RCA 1x S-Video 1x mini USB slave 1x USB Type-A 1x USB Type-B 3x Audio in 1x Audio out 1x RJ45 1x HDMI 1x RS232 1x Microphone 1x 12V DC relay output 1x antenna connector	1x AC power 2x D-Sub VGA-In 1x D-Sub VGA-Out 1x Composite Video RCA 1x S-Video 1x mini USB slave 1x USB Type-A 1x USB Type-B 3x Audio in 1x Audio out 1x RJ45 1x HDMI 1x RS232 1x Microphone 1x 12V DC relay output 1x antenna connector	1x Remote Control (basic infra-red remote control with page up / down w/o laserpointer) 1x Power Cord 1x VGA Cable 1x USB Cable (USB-A to USB-B) 1x Antenna 1x Interactive Pen 1x Mini USB Cable (USB-A to mini USB-B) 5x Nib 1x Wrist Strap 1x InterwriteWorkspace CD	1x Remote Control (basic infra-red remote control with page up / down w/o laserpointer) 1x Power Cord 1x VGA Cable	1x Remote Control (basic infra-red remote control with page up / down w/o laserpointer) 1x Power Cord 1x VGA Cable 1x Soft Carrying Case	1x Remote Control (basic infra-red remote control with page up / down w/o laserpointer) 1x Power Cord 1x VGA Cable 1x Soft Carrying Case	1x Remote Control (basic infra-red remote control with page up / down w/o laserpointer) 1x Power Cord 1x VGA Cable 1x Soft Carrying Case	1x Remote Control (basic infra-red remote control with page up / down w/o laserpointer) 1x Power Cord 1x VGA Cable 1x Soft Carrying Case 1x Antenna	1x Remote Control (basic infra-red remote control with page up / down w/o laserpointer) 1x Power Cord 1x VGA Cable 1x DisplayPort Cable

Other Features	Password Protection Option Quick Shutdown in 10 secs Auto Vertical Keystone Adjustment	Kensington Lock Slot Password Protection Option Customizable User Logo Quick Shutdown in 10 secs Closed Captioning Auto Vertical Keystone Adjustment	Kensington Lock Slot Password Protection Option Customizable User Logo Quick Shutdown in 10 secs Closed Captioning Auto Vertical Keystone Adjustment Supports 720p HD Format	Kensington Lock Slot Password Protection Option Customizable User Logo Quick Shutdown in 10 secs Closed Captioning Manual Vertical Keystone Adjustment Supports 720p HD Format Wall-mountable	Kensington Lock Slot Password Protection Option Customizable User Logo Quick Shutdown in 10 secs Closed Captioning Plug-and-Show USB Viewer PtG Converter Manual Vertical Keystone Adjustment Supports 720p HD Format Wall-mountable	Interactive Projection Kensington Lock Slot Password Protection Option Customizable User Logo Quick Shutdown in 10 secs Closed Captioning Plug-and-Show USB Viewer PtG Converter Manual Vertical Keystone Adjustment Supports 720p HD Format Wall-mountable	Kensington Lock Slot Password Protection Option Quick Shutdown in 10 secs Manual Vertical Keystone Adjustment Ceiling-mountable	Kensington Lock Slot Password Protection Option Quick Shutdown in 10 secs Manual Vertical Keystone Adjustment Ceiling-mountable	Kensington Lock Slot Password Protection Option Customizable User Logo Quick Shutdown in 10 secs Closed Captioning Auto Vertical Keystone Adjustment Ceiling-mountable	Kensington Lock Slot Password Protection Option Customizable User Logo Quick Shutdown in 10 secs Closed Captioning Auto Vertical Keystone Adjustment Ceiling-mountable	Kensington Lock Slot Password Protection Option Customized User Logo Quick Shutdown in 10 secs Closed Captioning Ceiling-Mountable Auto Vertical Keystone Adjustment	Kensington Lock Slot Password Protection Option Customized User Logo Quick Shutdown in 10 secs Closed Captioning Plug-and-Show Ceiling-Mountable Auto Vertical Keystone Adjustment	Kensington Lock Slot Password Protection Option Customizable User Logo Quick Shutdown in 30 secs Picture-In-Picture (PIP) Picture-By-Picture (PBP) Closed Captioning Ceiling-Mountable Auto Vertical Keystone Adjustment
3D-Capable <i>(Active 3D goggles with DLP Link, 3D player software application, HDMI/VGA cable, 3D content, PC/laptop with a 120Hz signal output quad buffered graphics card are required and sold separately)</i>	no	Yes	Yes	Yes	Yes	Yes	no	no	Yes	Yes	no	no	no
Wireless (PC must have a wireless card or be connected to a wireless network and have the projector software installed for proper function.)	no	no	no	no	YES Wireless Standard: IEEE802.11b/g - 4-to-1 split-screen projection; Multi-PC Sessions (up to 30 PCs); Conference Control	YES Wireless Standard: IEEE802.11b/g - 4-to-1 split-screen projection; Multi-PC Sessions (up to 30 PCs); Conference Control	no	no	no	no	no	YES Wireless Standard: IEEE802.11b/g - 4-to-1 split-screen projection; Multi-PC Sessions (up to 20 PCs); Conference Control	no
Crestron Roomview Compatible	no	no	no	Yes	Yes	Yes	no	no	Yes	Yes	Yes	Yes, by August 15, 2010	no